

"YOUR PRODUCT SOURCING PARTNER"

SOFAS LOVESEATS CHAIRS RECLINERS BARSTOOLS
TABLES FITNESS EQUIPMENT DRAPERIES BEDSPREADS
LAMPS FRIDGES COFFEE MAKERS ARTWORK ENCLOSURE
BLANKETS CUSTOM UPHOLSTERY CASE GOODS
LEATHERS EVERYTHING ELSE



SALES/MARKETING:
PHONE 1.780.909.7090

ADMIN/EXPEDITING:
PHONE 1.204.291.7411

Specifications: Bennett Sled Chair

Description: The Bennett chair is a classic library design available in a Sr. version (18"), and a Jr. (16") with scaled down proportions.

Dimensions: Bennett Sr. 18"

Overall Height	34.25"	87 cm
Overall Depth	20.5"	52 cm
Seat Height	18"	46 cm
Seat Depth	18.5"	47 cm
Seat Width	17.25"	44 cm
Chair Weight	24 lbs	10.9 kg
Carton Size for 1 chair		
	19.5" x 22" x 37.5"	
	49.5 cm x 56cm x 95.25 cm	
Carton Weight		
with 1 chair	34 lbs	15 kg

Dimensions: Bennett Jr 16"

Overall Height	29"	74 cm
Overall Depth	16.5"	42 cm
Seat Height	16"	41 cm
Seat Depth	14.5"	37 cm
Seat Width	13.5"	34 cm
Chair Weight	16 lbs	7.3 kg
Carton Size for 1 chair		
	17.5" x 17.5" x 33"	
	44.5 cm x 44.5 cm x 84 cm	
Carton Weight		
with 1 chair	26 lbs	12 kg

The Bennett sled chair is non-stacking. The space between the seat and the back measures 9" (23 cm).

Fabric for upholstered seat & back:

COM (Customer's Own Material)
fabric required: .5 yd

Note: This is the estimated amount based on 54" (137 cm) wide material and a quantity of more than 1 chair. The actual amount

required may vary depending on special pattern matching and the width of the material.

Cushion Foam: High density foam

Wood:

Species: 100% Solid European Beech Hardwood

Construction:

Joints: Mortise and tenon. Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root wood screws.

Stain Colors:

A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

9-Step Finishing Process:

1. The bare wood of the assembled chair is thoroughly sanded using 100 grit paper.
2. One coat of stain is sprayed onto the entire chair – including the underside of the seat.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.
4. The chair is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood – including the underside of the seat.
6. Once dry, the sealer is sanded using 280 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.

